



ANSI / DIN ref.	Pitch	Roller diameter	Width between inner plates	Pin diameter	Pin length		Inner plate depth	Plate thickness	Ultimate tensile strength	Weight per meter	
					L max	Lc max					
											chain no.
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kN/LB	kg/m
* 25ZP	6,35	3,30	3,18	2,31	7,90	8,40	6,00	0,80	3,50/795	0,15	
* 35ZP	9,525	5,08	4,77	3,58	12,40	13,17	9,00	1,30	7,90/1795	0,33	
41ZP	12,70	7,77	6,25	3,58	13,75	15,00	9,91	1,30	6,67/1516	0,41	
40ZP	12,70	7,95	7,85	3,96	16,60	17,80	12,00	1,50	14,10/3205	0,62	
50ZP	15,875	10,16	9,40	5,08	20,70	22,20	15,09	2,03	22,20/5045	1,02	
60ZP	19,05	11,91	12,57	5,94	25,90	27,70	18,00	2,42	31,80/7227	1,50	
80ZP	25,40	15,88	15,75	7,92	32,70	35,00	24,00	3,25	56,70/12886	2,60	
100ZP	31,75	19,05	18,90	9,53	40,40	44,70	30,00	4,00	88,50/20114	3,91	
120ZP	38,10	22,23	25,22	11,10	50,30	54,30	35,70	4,80	127,00/28864	5,62	
140ZP	44,45	25,40	25,22	12,70	54,40	59,00	41,00	5,60	172,40/39182	7,50	
160ZP	50,80	28,58	31,55	14,27	64,80	69,60	47,80	6,40	226,80/51545	10,10	
04BZP	6,00	4,00	2,80	1,85	6,80	7,80	5,00	0,60	3,00/682	0,11	
05BZP	8,00	5,00	3,00	2,31	8,20	8,90	7,10	0,80	5,00/1136	0,20	
# 06BZP	9,525	6,35	5,72	3,28	13,15	14,10	8,20	1,30	9,00/2045	0,41	
08BZP	12,70	8,51	7,75	4,45	16,70	18,20	11,80	1,60	18,00/4091	0,69	
10BZP	15,875	10,16	9,65	5,08	19,50	20,90	14,70	1,70	22,40/5091	0,93	
12BZP	19,05	12,07	11,68	5,72	22,50	24,20	16,00	1,85	60,00/13636	1,15	
16BZP	25,40	15,88	17,02	8,28	36,10	37,40	21,00	4,15/3,1	95,00/21591	2,71	
20BZP	31,75	19,05	19,56	10,19	41,30	45,00	26,40	4,5/3,5	95,00/21591	3,70	
24BZP	38,10	25,40	25,40	14,63	53,40	57,80	33,20	6,0/4,8	160,00/36364	7,10	
28BZP	44,45	27,94	30,99	15,90	65,10	69,50	36,70	7,5/6,0	200,00/45455	8,50	
32BZP	50,80	29,21	30,99	17,81	66,00	71,00	42,00	7,0/6,0	250,00/56818	10,25	

*Bushing chain: d1 in the table indicates the external diameter of the bushing.

Straight side plates.

Double strand zinc plated chains are available in all sizes.